

# Test Kit 300.15

## Model 300.15

Designed for use by Consulting Engineers and Mechanical System Operators.

### Kit includes the following products:

- G160** Pressure Gauge
- GA18** Gauge Adapter
- GA30** Gauge Adapter
- PL2** Probe Lubricant
- TCF220** 0° - 220°F (-10° - 100°C)



## Product Information

### Model GA18

Standard length adapter for use with standard P/T port. Has 1/4" FPT connection. Used primary for pressure gauges, but can be used for venting, sampling, etc.

### Model GA30

Same as Model GA18, but probe is longer for use with extended P/T ports.

### Model TCF220

Dial Stem Thermometer. 1-3/4" dial, recalibration nut, 5" stainless steel stem, for use with any P/T port. Model TC220 has a dual scale, 0 to 220° F and -10 to 100° C. Accuracy is  $\pm$  one division.

### Model G160

Pressure gauge, 3-1/2" face. Scale reads 0 to 160 PSI and to 1100 KPA. 1/4" bottom connection matches GA18 and GA30 adapter. Accuracy is +3%.

### Model PL2

Special silicone lubricant. Used on gauge and thermometer probes in accordance with operating instructions.



*The products, texts, photographs, graphics and diagrams in this document may be subject to alteration by IMI Hydronic Engineering without prior notice or reasons being given. For the most up to date information about our products and specifications, please visit [www.flowdesign.com](http://www.flowdesign.com).*